

# Your watercraft has been enhanced and customized with revolutionary Vantage Protection Products including Vantage Pontoon Wrap<sup>™</sup>, Vantage Pontoon Guard<sup>™</sup>, and Vanage Protection Film<sup>™</sup>.

Upon Completing This Form a PDF version of the warranty will be sent to the email address provided.

#### YOU MUST RETAIN THIS WARRANTY CARD TO VALIDATE YOUR WARRANTY

Vantage Combo Kit (Pontoon Wrap + Guard)		Vantage Pontoon Guard		
Vantage Protection Film	Vantage Pontoon Wrap			
Boat: Make:	_ Model: _			Year:
Boat: Vin#:		Installation Date:	_!!	
Dealer: Name:	Phone: _		City/State	
Certified Installer:	S	ervice Manager:		
Customer Info: Name:		Phone:		
Address:	Cit	ly:	State:	Zip:
Email:				

#### The Vantage Protection Products Watercraft Owner Warranty

Limited Warranty and Limited Remedy: Vantage Resource Group (VRG) warrants that applied Vantage Protection Products will be free of defects in materials and manufacture for five (5) years from the date of purchase. This warranty applies to the above-the-waterline application only. Below/under water applications are not covered under this warranty. This warranty does not apply to damage caused by misuse, accident, misapplication, or ordinary wear, nor does it apply to dents caused by physical impact or rock debris. This warranty is provided only to the original purchaser and is not transferable. Vantage will replace Vantage Protection Protection Product piece(s) if adhesion failure occurs (1 time). Vantage will not be responsible for labor to remove or replace the defective or damaged product.

**Making a Warranty Claim:** To make a claim under this warranty in the United States, simply contact VRG at 877.477.3456. VRG will require photo(s) of the defective product. In some cases VRG may require the defective product be returned for inspection.

**Implied Warranty Limitation:** ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OR CONDITIONS OF MERCHANTABILITY, THE IMPLIED WARRANTY OR CONDITION OF FITNESS FOR A PARTIC-ULAR PURPOSE, AND ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE, ARE LIMITED IN DURATION TO THE APPLICABLE WARRANTY TIME PERIOD. Some states jurisdictions do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.

**Limitation of Liability:** Except where prohibited by law, VRG shall not be liable for any loss or damage arising from the Vantage Protection Product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states do not allow the exclusion of limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

#### **Care Instructions:**

• Vantage Protection Products are easy to care for. You can use your watercraft as early as 36 hours after installation.

### **Hand Washing:**

- Flush the product with clean water to remove loose dirt particles. A trigger-type hose nozzle is convenient for this purpose.
- Use a marine grade cleaner and water solution and wash the wproduct with a soft brush, rag or sponge. Wash thoroughly from the top down.
  Avoid abrading the product by unnecessary scrubbing.
- After applying the cleaning solution, keep a steady stream of water flowing on the product to wash away dirt particles.
- Rinse the entire product thoroughly with clean water. Allow to dry naturally.

## **Removing Difficult Contaminants:**

Special care must be taken to avoid abrading or scratching the product Scratching and abrasion marks may be Arisible and you may not be able to work them out of the unique finish of the wproduct. To help avoid such damage Avoid using harsh chemicals, brushes or hard scrubbing when cleaning the product and avoid parking near shrubs and trees or any other items that could scratch the product. Rinse shoroughly after cleaning and dry with a clean, soft cloth or soft rubber squeegee to avoid water spots. Do not apply waxes, polishes, paint or clear coat over the product. If there is wax and wax residue on the product remove Awith an all-purpose cleaner. To help restore the finish of the product, clean it with isopropyl alcohol and water (2:1ratio). Some contaminants may remain after following the normal cleaning procedures. Most contaminants can be removed using one of these methods. Other cleaning products and methods should be used only on a customer test-and-approve basis. 1. To remove tar, oil, diesel smut or bituminous material: • Wipe with 3M<sup>™</sup> Citrus Base Cleaner or a rag dampened with kerosene, mineral spirits, heptane, or VM&P naphtha. Do not use other solvents. 2. To remove pollen and fungus: • Wash the product with 3M™ Marine Mildew Stain Remover (PN 09067), a 3 to 5% sodium hypochlorite (full-strength household bleach) solution, or mild liquid detergent and water. • Rinse with clean water immediately. 3. To protect the product from pollen and fungus, apply 3M<sup>™</sup> Marine Mildew Stain Remover as a part of regular maintenance: • Remove any existing mildew stains. Clean and dry the surface. Using 3M™ Marine Mildew Block (PN 09065), spray surface and gently wipe to ensure a uniform coating over the product, including the edges. Ensure a uniform coating without leaving droplets, streaks, or puddles. Remove any over-spray with a damp cloth, and allow to dry (typically for one hour). Repeat after cleaning\*. \*Use of some cleaners can remove the protective coating and reduce the length of product protection. • Select an appropriate solvent and test it in an inconspicuous area to ensure it removes the contaminant without damaging the wrap and guard. This must be done on a customer test and approve basis. Wash immediately with marine grade cleaner and water, then rinse with clean water.